

Installation Guide Smart-UPS[™] C 1000/1500 VA 120/230 Vac Tower

Important Safety Messages

Read the instructions carefully to become familiar with the equipment before trying to install, operate, service or maintain it. The following special messages may appear throughout this manual or on the equipment to warn of potential hazards or to call attention to information that clarifies or simplifies a procedure.



The addition of this symbol to a Caution product safety label indicates that a hazard exists that can result in injury and product damage if the instructions are not followed.

The following safety messages may appear throughout this manual to warn of potential hazards.

CAUTION

CAUTION indicates a potentially hazardous situation which, if not avoided, **can result in** equipment damage and minor or moderate injury.

CAUTION

CAUTION indicates a potentially hazardous situation which, if not avoided, can result in equipment damage.


Safety and General Information

Inspect the package contents upon receipt. Notify the carrier and dealer if there is any damage.

Read the Safety Guide supplied with this unit before installing the UPS.

- Adhere to all local and national electrical codes.
- This UPS is intended for indoor use only.
- Do not operate this UPS in direct sunlight, in contact with fluids, or where there is excessive dust or humidity.
- Be sure the air vents on the UPS are not blocked. Allow adequate space for proper ventilation.
- The battery typically lasts for two to five years. Environmental factors impact battery life. Elevated
 ambient temperatures, poor quality utility power, and frequent short duration discharges will shorten
 battery life.
- Connect the UPS power cable directly to a wall outlet. Do not use surge protectors or extension cords.
- The batteries are heavy. Remove the batteries prior to installing the UPS in a rack.
- Refer to **Specifications** in the Operation manual for UPS and battery weight.


Inventory



Product Overview


Rear panel features

1000/1500 VA 120 Vac models




- USB port
- 2 Serial data port
- **3** Battery connector

1000/1500 VA 230 Vac models



- 4 Circuit breaker/Overload protection
- **5** UPS input
- **6** Outlets
- Chassis ground screw


Front panel features



- Online/On Battery LED
- 2 POWER ON/OFF button
- **3** Site Wiring Fault/System Fault LED
- 4 Display interface
- DISPLAY button
- 6 MUTE button

Installation

Connect the battery




Connect equipment to the UPS and connect the UPS to utility power

CAUTION

RISK OF EQUIPMENT DAMAGE

- Adhere to all local and national electrical codes.
- Wiring should be performed by qualified electrician.
- Always connect the UPS to a grounded outlet.

Failure to follow these instructions can result in equipment damage





Select models are ENERGY STAR $^{\circledR}$ qualified.

For more information go to www.apc.com/site/recycle/index.cfm/energy-efficiency/energy-star/