

# Product datasheet

Specifications



## Wired, Sensor, NetBotz, 2 Door Switch Sensor

NBES0303

### Overview

Presentation	Universal Sensor that monitors access to NetShelter SX Enclosures.
Lead time	Usually Ships within 2 Weeks

### Main

product or component type	Sensor
Range of product	Netbotz
Provided equipment	Cable ties
Product compatibility	4 - 20 mA sensor Rack sensor pod 150 Room sensor pod 155 Sensor pod 120 NetBotz USB camera pod Pelco IP110-CHV9

### General

Display resolution	Up to 640x480
Connections supported	Alarm beacon 1 PS/2 mini-DIN
Universal sensor supported	Door contact Humidity Smoke Temperature
Number of universal sensor ports	2
Number of sensor pods supported	0
Number of universal sensors supported	0
Sensor humidity	10...90 % +/- 5 % non-condensing RH
Number of supported camera	4 for networked 4
Measurement range	1.6...48.8 °C: +/- 1 °C 35...120 °F:

### Physical

Height	1.9 cm
Width	14.6 cm
Depth	18.7 cm
Net weight	0.37 kg
Mounting preference	No preference

---

Mounting mode	Not rack-mountable
---------------	--------------------

## Output

---

Number of port	0
----------------	---

## Environmental

---

Ambient air temperature for operation	0...45 °C
---------------------------------------	-----------

---

Operating altitude	0...10000 ft
--------------------	--------------

---

Relative humidity	0...95 %
-------------------	----------

---

Ambient air temperature for storage	-15...65 °C
-------------------------------------	-------------

---

Storage altitude	0.0000000000...15240.0000000000 m
------------------	-----------------------------------

---

Storage Relative Humidity	0...95 %
---------------------------	----------

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Number of Units in Package 1	1
------------------------------	---

---

Package 1 Height	4.8 cm
------------------	--------

---

Package 1 Width	23.2 cm
-----------------	---------

---

Package 1 Length	16.4 cm
------------------	---------

---

Package 1 Weight	0.489 kg
------------------	----------

## Contractual warranty

---

Warranty	2 years repair or replace
----------	---------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

## Well-being performance



Reach Free Of Svhc

---

### Reach Regulation

[REACH Declaration](#)

---

### Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

---

### Weee

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

---